INDIANA'S HIGHWAY NEEDS STUDY


DEC., 1957 NO. 35

by

D.O. Covault

reject

PURDUE UNIVERSITY LAFAYETTE INDIANA



TECHNICAL PAPER

"INDIANA 'S HIGHWAY NEEDS STUDY"

TO:

K. B. Woods, Director

Joint Highway Research Project

December 18, 1957

FROM:

H. L. Michael, Assistant Director

File: 3-3-20 Project C-36-54T

Attached is a technical paper entitled, "Indiana's Highway Needs Study," by D. O. Covault, Research Engineer on our staff. This paper will be presented at the 37th Annual Meeting of the Highway Research Board in Washington, D. C. in January, 1958.

The paper summarizes the planning and procedures utilized for the Indiana Highway Needs Study. It also includes the major findings of the study and discusses the needs found.

The paper is presented for the record.

Respectfully submitted,

Harold & michael

Harold L. Michael, Assistant Director Joint Highway Research Project

HLM: hgb

Attachment

cc:	A_{\circ}	Ko	Branham	R.	D_{\circ}	Miles
	Jo	R.	Cooper	R.	E.	Mills
	M.	L_{o}	Dolch	B.	H.	Petty
	M.	H.	Goetz	M.	В.	Scott
	Jo	To	Hallett	C.	E.	Vogelgesang
	F.	\mathbb{F}_{\circ}	Havey	Jo	\mathbf{L}_{c}	Waling
	G.	A.	Hawkins	J o	$\mathbf{E}_{\mathbf{c}}$	Wilson
	G,	Ao	Leonards	E.	Jo	Yoder
	J.	F.	McLaughlin	_		

. e de la companya de l The second secon •

TECHNICAL PAPER

"INDIANA'S HIGHWAY NEEDS STUDY"

by

D. O. Covault Research Engineer

Joint Highway Research Project File: 3-3-20 Project C-36-54T

Purdue University Lafayette, Indiana

December 18, 1957

Digitized by the Internet Archive in 2011 with funding from LYRASIS members and Sloan Foundation; Indiana Department of Transportation
http://www.archive.org/details/indianashighwayn00cova

University has conducted research in various phases of highway engineering in cooperation with the Indiana State Highway Department. Research has been conducted in many areas of highway materials and traffic and planning during this time. In the summer of 1954, the Research Project was directed to make a study of the needs of the 98,000 miles of roads and streets in Indiana (See Figure 1). It was evident to many people that a great many inadequacies and deficiencies existed in the highway facilities, but it was necessary to have definite information about the specific needs in order to intelligently solve the resulting complex engineering and fiscal problems. Generally, the efforts of the early planning of the work were directed to the solution of the following problems:

- 1. What are the physical needs?
- 2. How much will correction of the needs cost?
- 3. What is the relation of the cost required to eliminate the needs with anticipated sources of income for highway improvement?

The final objective in answering these three basic questions was to develop information that would assist highway and legislative personnel provide an adequate, efficient, and economical highway system in Indiana.

No attempt was made to solve the financial problems which a study of this nature would reveal. The research was confined primarily to an engineering appraisal of the physical needs and the costs required to eliminate these needs. Other questions which were related to the

		•	

determination of deficiencies and related costs, however, had to be considered. Such problems as economic services of the highway, growth trends, classification, accidents, traffic operations, length of program periods, and other problems were evaluated along with the determination of the direct needs.

Collecting Data

During the early fall of 1954 and winter of 1955, a complete physical inventory of the 10700 miles comprising the State Highway System was made by State Highway Department personnel. Each of the six highway districts could readily supply the necessary personnel to rapidly complete this inventory within a few months because of the "elack season" between the 1954 and 1955 construction seasons. By the last spring of 1955, all inventories were substantially finished.

The actual procedures and techniques for making the inventory were developed by the Research Project. Essentially the information that was required can be broken down into three general categories:

- l. Road or street information
- 2. Bridge information
- 3. Railread crossing information

The read information that was collected is indicated by Figures 2, 3, and 4; bridge information by Figure 5; and railread crossing information by Figure 6. Actually, a great deal more information was collected than was absolutely required for the performance of a needs study. However, this additional information was collected for a definite purpose. For instance, data concerning readside development

•			

of various types can be used to help determine the service characteristics of the highway and some of the effects of roadside development on the movement of traffic. Sufficiency ratings for the rural highways were also computed from some of the information, which was not directly involved in the needs appraisal.

Traffic data for each section of highway were placed on the inventory information. Accident rates per 100 million vehicle miles, were somputed from accident records obtained from the State Polline Department and traffic data for the particular rection of road. To a information was also added to the inventory data.

It was not possible to make extensive inventories of the study and sity and sounty systems; and, therefore, other sources of data were used to develop and evaluate the needs on these systems.

Presedure of Analysis of Lats

Before actual study of the data was started, a thorough evaluation of growth trends of population, motor vehicle registration, motor vehicles use, motor fuel consumption, and traffic growth was undertaken. The resulting traffic growth curve for the State Highway System is indicated in Figure 7. The upper line indicates the maximum possible growth of traffic, and the lower line indicates its probable average growth. The lower line was computed on the basis of the "least squares method" derived from the extention on past traffic data. The upper line was computed by the "three factor method" which considered the growth of population, motor fuel consumption, and mater vehicle registration.

	•			

Development of tolerable and design standards required much thought and work. Many meetings with the State Highway Department and other qualified engineers were necessary to produce an acceptable set of standards for new construction and tolerable conditions. Development of standards for the rural state and county systems wis comparatively easy; however, it was not possible to develop a formal set of standards for the urban state highways and city streets because of the complexities of the transportation problem in a great many of these areas. Typical examples comparing some of the chements of tolerable and design standards for the rural state primary and secondary and county primary systems are indicated in Figures 8 and 5.

Construction cost data for the State Highway System were based on state-wide average costs for various types of highway in proviment.

These costs were obtained through the cooperation of the State Highway Espartment and, therefore, accurate, unable data was determined.

The development of existing costs of maintenance and the costs of adequate maintenance was also accomplished by this organization.

Development of cost data for the county road and city street systems, however, was indeed difficult. Cost records were virtually non-existant in many of the smaller cities and many of the counties. It was necessary, therefore, to base most of these costs upon estimation and expert judgement.

Since the inventory was to serve the multiple purpose of providing statistical information for other uses than a Needs Study, it was decided to place all of the information on IBM punch caris. The punch cards also provided the most efficient and quick means of analysis of the multitude of data which was necessary to process.

Two cards were punched for each highway section containing all pertinent road information. A card was also punched for each bridge and railroad crossing which was contained in the highway section. Additional information, which could not be taken by the inventory crews, such as traffic capacity, accident rate, and soil type was also determined and punched into the cards.

Work sheets for each section of road, and the bridge and railroad crossing, which were located in the section were tabulated as indicated in Figure 10. Existing deficiencies were indicated on the work sheets as well as anticipated future deficiencies. The year of needed improvement was then determined and construction recommendations were made. The cost of the improvement was then determined based on average construction costs previously determined.

Needs on the Interstate System were not determined in this manner since the State Highway Department had nearly 50% of proposed Interstate System in the final stages of the preliminary design. Costs that were developed for rural and urban portions of this work were used to determine the entire cost of the system.

metropolitan areas were developed on the basis of recommendations given in several of the recent comprehensive traffic surveys which have been conducted in Indiana and long range city plans. The city planner was found to be an essential individual in the determination of urban needs. His knowledge of urban growth is a particular community greatly influenced the determination of arterials streets and the traffic flows on these streets. Therefore, long range city plans were used extensively in those cities where such information was developed.

	,		
			- 1

It was impossible to inventory each mile of the 87,300 miles of county roads and city streets because of time, financial and staff limitations. Furthermore, the available records of construction and plans for county road and city street improvements were found to be inadequate. Useable cost information in most of the counties and smaller and intermediate size cities was also difficult to locate. In fact, this very lack of information indicated one of the major needs on the county and city road systems, even though these needs cannot be directly evaluated in terms of dollars and cents.

To help solve the problem of lack of adequate data, it was decided to use any available information concerning the city and county systems which was accessible. Since most of the county road and city street system were not classified, the difficulty of this problem was increased.

Therefore, the first step was to classify the 76,000 miles of county roads into Primary, Secondary, and Local road systems. Data from recent road classification studies that were performed in two Indiana Counties and other road classification data available from studies made elsewhere indicated that 13 percent of the total county mileage was located on the Primary system and 12 percent was located on the Secondary system.

Various composite estimates of the dollar needs required on the Primary, Secondary and Local road systems were determined from the information available in these two counties and from a study of county road needs in adjoining states as reported in their recent needs studies.

To classify the 11,300 miles of city streets which were located

	1		
		•	

on the arterial and residential systems, the total mileage on these systems were determined from a sample of cities of various population classes. From this study it was determined that an overall average of approximately 25 percent of the city street mileage was located on the Arterial system and the remaining 75 percent on the re-idential system.

Composite needs on these two systems were then determined from various engineering studies made previously of several cities in Indiana and from recent needs studies performed in adjacent states.

Construction of residential streets in new subdivision development in both the counties and cities were not considered as a highway needs since laws in these governmental units required that these roads and streets be constructed by the land developer or property owner to standards which meet the minimum design requirements for this study. Increased maintenance needs, however, were considered because of the growth of mileage on these systems.

Although the county road and city street needs were determined from data which are not as objective as that for the state highway system, the needs were based on the best available information and are considered to be realistic and adequate.

SUMMARY OF RESULTS

Description of Needs, Program Period, and Price Adjustment

Some of the preliminary tabulation of data from the inventory information revealed that the needs on the Indiana System of highways would be great. Inadequate pavement and shoulder widths, inadequate

		٠
		,

traffic capacity on the major systems, may narrow and overload bridges, and several other types of functional and structural obsolescence were indicated. Most of this preliminary data tentatively proved what has been known for many years - many inadequacies existed on the highway system and these deficiencies would be great. Furthermore, the needs that would accrue in the future years would create still greater problems.

The physical needs were divided into the conventional categories which have been used in previous work: immediate needs, future needs, and maintenance needs. Included in the future needs were replacement and stop-gap improvements. Maintenance needs also included the administration requirements.

A program period of 15 years was chosen for this study because of influence of the 1956 Federal Aid Highway Act and because it was thought that engineering and construction requirements could be most effectively fulfilled during such a program period. A longer or shorter program did not seem practical, and therefore, physical needs and costs were not determined for other periods of time. The estimate of costs for improvements were based on 1955 prices, and adjustments for possible future price trends were not attempted.

State System

With the exception of the toll road, very few miles of the proposed 1,100 miles of Interstate System in Indiana meet approved design standards. Nearly 932 miles of this system must be relocated in the next 15 years. Four-lane divided construction is needed on

		•	

all rural highways, and in some of the urban areas six-lane freeway construction is required. According to data developed for this study a total expenditure of \$881 million will be required on this system. These figures have been revised to \$1,058 million by the recently completed Section 108(d) study.

Needs found on Rural Primary, Secondary, and Urban Systems were also great. On the rural system over 30 percent of the existing mileage are in immediately need of improvement. During the next 15 years an additional 65 percent of the mileage will become inadequate. The complex problem of the Urban State Highways must be handled boldly and decisively since the present needs are critical. Congestion and delay are becoming more prevalent as each day passes. During the next 15 years over 350 miles of by-passes will be required around these areas. Expressway systems are needed in the state's larger cities.

The total cost of the construction work necessary eliminate the immediate and future needs on the Rural and Urban Systems is \$1781 million. Additional funds that are required for the maintenance and administration needs amount to \$354 million.

County Road System

As would be expected, the greatest needs on a cost per mile basis occurred on the Primary and Secondary systems. Generally, these roads carry traffic volumes between 100 to 1000 vehicles per day and are composed of farm to market traffic and carry milk, postal routes, and other important county traffic flows. The Local County systems consist mainly of farm access and residential access roads, with the

	~			
		-		

origin-destination of traffic being primarily of short, local trips. In order to eliminate the present and future needs over the next 15 years construction expenditures of \$372 million on the Primary and Secondary systems and \$161 million on the Local road system are required. An additional expenditure of \$458 million is required for maintenance and administration on all systems

City Streets

The needs on the Urban State Highways are not included in this discussion, since they have been reviewed earlier on the State Highway System. During the next 15 years, it is estimated that early 41 percent of the mileage on the Arterial System and 59 percent of the mileage on the Residential System must be resurfaced or reconstructed. Nearly \$237 million is required for construction on the Arterial streets and \$207 million is required for construction of the Lesal streets to eliminate present and future needs. Maintenance and administration will require additional expenditure \$206 million during the 15 year period.

A summary of the average annual expenditures estimated for the state, county, and city systems for a 15-year program is presented in Figure 11. The costs for the Interstate System have been separated from the costs of the other State Systems because of its uniqueness and high cost of construction. As can be seen from the chart, the average annual cost for a 15-year program eliminate the needs on the State Rural and Urban Primary and Secondary systems is \$156 million; the Interstate, \$81 million; the county system, \$66 million; and the

city street system, \$43 million. The total estimate average annual expenditure required for all systems for 15 years is \$346 million.

Needs Versus Finances

Indiana obtains revenue for construction, maintenance, and administration of its highway system primarily from motor fuel taxes, license and registration fees, local county or city funds, and Federal Aid. In 1955 a total of \$108 million was available from these sources. With the passage of the Federal Aid Revenue Act of 1956 and a recent two-cent increase in state motor fuel taxes, a significant change has occurred in the availability of highway funds in Indiana. Estimates of revenues during the next 15 years have been developed from present growth trends and revenue policies are shown in Figure 12. It is estimated that the annual highway income will reach a peak of \$280 million by 1967, and that it will be reduced to \$250 million by 1971 because of reduction in Federal Aid due to the completion of the Interstate System.

Superimposed on the estimated income curve is a suggested curve that indicates the yearly expenditures which are required to eliminate the needs. This curve is derived by assuming that the average yearly income to eliminate the needs minus Federal-Aid will be attained in the middle of the fiscal year 1964 (1/2 of total 15 year program). The yearly state revenue is then assumed to increase at a rate of \$12 million a year from this point until the end of the fiscal year 1971, and decrease at a rate of \$12 million a year from this point until the beginning of the fiscal year 1957. The upper curve is finally obtained by adding the

anticipated Federal Aid during this program period to the required state revenues necessary to eliminate the needs

It is obvious from Figure 12 that the required needs will not be satisfied by the anticipated funds. In fact an additional 1.4 billion will be required over and above that which can be provided by present sources of revenue. Either new sources of revenue will be required or increases in old sources will be needed to fill the gap between needs and available finances.

Concluding Statement

The concepts and procedures that were used on the Needs Study along with some of the results have been presented. It is difficult to determine the total impact of an adequate highway system on the general economy of the state but many benefits to the highway user and non-highway user will result.

Although not mentioned specifically in this paper, careful consideration was given to those needs which could not be measured on a monetary basis. Improve traffic operations through effective traffic engineering, wise and efficient use of off-street parking facilities, classification of roads and streets, improved cost accounting, the supply of engineer and technicians, road-classification and a number of other problems were evaluated as to the effect on the total needs problem. Having adequate funds and adequate planning to eliminate highway deficiencies is not enough to do a complete job; consideration and solutions to problems as have just been outlined must also be attained.


	0		
	٠		
			•
			-

SELECTED REFERENCES

- A. K. Branham, D. O. Covault, and H. L. Michael, "Progress Report on State Highway Needs in Indiana," <u>Profeedings of the</u> <u>42nd Annual Road School</u>, Purdue University, April, 1956.
- 2. D. O. Covault, H. L. Michael, and A. K. Branham, "Summary Report on State Highway Needs in Indiana," Proceedings of the 43rd Annual Road School, Purdue University, April, 1957.
- Automotive Safety Foundation, An Engineering Study of Ohio's Highways, Roads, and Streets, published in 1950.
- 4. Automotive Safety Foundation, A Highway Program for Kentucky, published in 1955.
- 5. Automotive Safety Foundation, Modern Highways for Michigan, published in October, 1955.
- 6. Automotive Safety Foundation, <u>Highway Transportation in Tennessee</u>, published in November, 1955.
- 7. Indiana State Highway Commission, <u>Highways of Indiana</u>, published in 1948.
- 8. Griffenhagen and Associates, A Highway Improvement Program for Illinois, published in 1948.
- 9. John E. Baerwald, <u>Rural Highway Classification and Evaluation Procedures for Indiana Counties</u>, Phd. Thesis, Purdue University, January, 1956.
- 10. State Highway Department of Indiana, Richmond Indiana Traffic Survey Report, published 1954.
- 11. State Highway Department of Indiana, Evansville, Indiana Traffic Survey Report, published 1950.
- 12. State Highway Department of Indiana, Princeton Indiana Traffic Survey Report, published in 1953.
- 13. State Highway Department of Indiana, Calumet District Traffis Survey Report, published in 1953.
- 14. State Highway Department of Indiana, Indianapolis, Indiana Traffic Survey Report, published in 1952.
- 15. State Highway Department of Indiana, Highway Plan for Fort Wayne, Indiana, published in 1946.

·	
	•
	10.74
	:

14



INDIANA'S

HIGHWAY

PROBLEM

FIGURE I



GENERAL INFORMATION AND DATA SHEET

i.	ž	SO		ř		+		Do Nor Filt In)	F111 (a)
District	Route			Maint. Sec	tion	- Length		Classification	
County				Interstate	Dote	ļ	of .	ADT	DHV
Gity				Secondary 16.	_ Party Chief _			Cameity	
Start of Section				Other Fed.	_ 17. _ Recorder			Type of Traffic	
8. End of Section				Non. Fed.	— 18.				
9.		Į		The of Median				-	2.
Orrection of Travel				19 pe or med Width of Med	liei-			3.	•
	Povement	+ Nistory		20. Sket	20. Sketchof Typical Cross Section	ross Section		5.	6.
Structurel Element M	Material	Thickness	- 1	¥•04				7.	8.
								9.	10.
				T -				n.	12.
				- 				13.	14.
								15.	16.
								17.	16.
								19.	20.
								21.	22.
21-Sketch Plan View of Maint. Section	int. Section	 			 			23.	24.
								25.	26.
								27.	28.
								29.	30.
								31.	32.
								33.	34.
								35.	36.
								37.	38.
22'General Description								39.	40.
									42.
					1			43.	;
								45.	46.
Overall								47.	48.

	ī	

FIGURE 3

	anada.						_	7		_				7					7	
39.	But City Stan						1													
	Topography Safe Driying	+				+	+-		_		-			+-	+		-			_
38		/ 	+		-	-	-		+	-	\rightarrow	+	+	+	-	-	-	-	\vdash	_
	Dessing Deportunities	\bot			\rightarrow	\perp	1					\rightarrow	-	-	-	_		_		
36.	Vertical Slaht Distance																			
	Gradians																			
33.	memagilA	1	+	\vdash			+-			-	\rightarrow	+	-	+-	-	-		-	-	
7	[atnox ino H																			
33.	Drehode	T																	i	
F-	Right H	+			-+	+	1		+			_		1	+	-		1		
Ш				\vdash	-	-	+	-		-	-	-		+	-		_	-	-	_
.	c ∺ ++•1								_		1_									
:	Bees % Surface %																			
1 2	enulia 1	1	_	\vdash	-		+	 		-			+-	+		_				_
0	S eas 8	4	+	\vdash	-		 			-				-	-	-	_	-		_
	Surface &																			
	. Mediam													ĺ						
1]~		+-			+	+		+	 	\dashv	\rightarrow	_	+	+	-		 	1	_
											- 1									
5		1														ì				
5																		ł		
Necorder -																				
																-				
11	•					1					ĺ									
ll	S e e										-							 		
	ž																			
\parallel			}																	
<u>ו</u> 'פ																		İ		
3						i					1									
		1					1	1 (- 1			- }								
.1													- 1	l l	1	i .		-	1 1	
																				
	e ter				<u> </u>		-		 	-			 							-1-
26.	domater double																			
26.	25. Ddometer Reading																			
26.	6 7																			
26.	6 7						-													
26.	Arrening 2																			
26.	Milea 24. 2 Intervening Distance																			
Mileon 26.	Z4. 24. Distance																			
23. Milesse 26.	Speed 24. 24. 22. 2 Distance																			
23. Milesse 26.	beed? 24. 27. 27. 27. 27. 27. 27. 27. 27. 27. 27																			
23. Milesse 26.	gnised-oV beed? Son Z Bando A Disconting C C C C C C C C C C C C C																			
[23. Milega [26.	boods Soils 24. Soils 24. Soils 24. Soils 24. Soils 25. Soils 26. Soil																			
23. Milesse 26.	boods Soils 24. Soils 24. Soils 24. Soils 24. Soils 25. Soils 26. Soil																			
23. Milesse 26.	Reiding Sweece Coward Coward No-Possing Zone Speed Speed Soning The Speed Coming The Speed The																			
20. 21. 22. 23. Mileson 26.	Rights 5-5 Shoulder Shoulder Riding Surfece Type Council Reili Speed Soning Soning Soning Speed Soning Speed Soning Speed Soning Speed Soning Speed Spee																			
20. 21. 22. 23. Mileson 26.	Rights 5-5 Shoulder Shoulder Riding Surfece Type Council Reili Speed Soning Soning Soning Speed Soning Speed Soning Speed Soning Speed Soning Speed Spee																			The state of the s
20. 21. 22. 23. Mileson 26.	Rights 5-5 Shoulder Shoulder Riding Surfece Type Council Reili Speed Soning Soning Soning Speed Soning Speed Soning Speed Soning Speed Soning Speed Spee																			
20. 21. 22. 23. Mileson 26.	Country of the countr																			
Width 20 21 22 23 Milens 26	Rights 5-5 Shoulder Shoulder Riding Surfece Type Council Reili Speed Soning Soning Soning Speed Soning Speed Soning Speed Soning Speed Soning Speed Spee																			
Width 20, 21, 22, 23, Mileon 26,	Right - 55 Left - 7 Shoulder																			
Width 20, 21, 22, 23, Mileon 26,	Right - 55 Left - 7 Shoulder																			
Width 20, 21, 22, 23, Mileon 26,	Entrences To Highway Alghray Colored Shoulder Shoulder Shoulder Shoulder Type Counce Shoulder Type Counce Type Counce Type Counce Speed A Zone Speed Zone Zone Speed Zone Zone Zone Zone Zone Zone Zone Zone																			
Width 20, 21, 22, 23, Mileon 26,	Carplein) Explein) Envences To Highwey Right: 5 Left 3 Shoulder: 7 Shoulder: 7 Shoulder: 7 Right: 6 Coard Reil Rei																			
Width 20, 21, 22, 23, Mileon 26,	Carplein) Explein) Envences To Highwey Right: 5 Left 3 Shoulder: 7 Shoulder: 7 Shoulder: 7 Right: 6 Coard Reil Rei																			
Width 20, 21, 22, 23, Mileon 26,	Form Doubling Consults of Cons																			
15. Width 20. 21. 22. 23. Milena 26.	Emening Shoulder To Highing Shoulder To Maching Shoulder To Machin																			
15. Width 20. 21. 22. 23. Milena 26.	Emening Shoulder To Highing Shoulder To Maching Shoulder To Machin																			
15. Width 20. 21. 22. 23. Milenda 26.	Monthly and a stablishment in dustwind in																			
15. Width 20. 21. 22. 23. Milenda 26.	Monthly and a stablishment in dustwind in																			
15. Width 20. [21. [22. [23. Milende 26.	Monthly and a stablishment in dustwind in																			
15. Width 20. [21. [22. [23. Milende 26.	School Sc																			
15. Width 20. 21. 22. 23. Milenda 26.	Monthly and a stablishment in dustwind in																			

RURAL STATE HIGHWAY INVENTORY DATA SHEET

				,	
				ą.	
		,			
	,				
			•		
-					

FIGURE 4

			-		_	_	_	7	7	_				, ,	_			_			$\overline{}$		
	Safe Driving											- 1											
-	Effectiveness of Treffic Cont.Davic																						
	Credient C	+-+	+-							_			_			-							
E.	Beenland.	\vdash				_	_									\rightarrow			-				
Ë	Highway																						
	Surface										Ì					ĺ	ĺ			1			
			-													$\overline{}$							
:	Surface of the control of the contro		-	-	_			-			_					-				-		_	
1 11	Sec egptwe																						
'	Median N										ĺ												
	_18	 	_																				
												-											
5																							
Recorder												j											
اچُ																							
ا آ																							
				i l																			
																1							
	8																						
	Notes								[
	_																						
Date		i																					
التام																							
]		1																					
															- 1								
3 6																							
		1		Ή	Τ,	Т	Т	Т	Т	7	7	\top	7	\top	Τ,	- + +							
i II	6. Odometer Reading	-		- -	- -	+	┥-	- -	- 🕇 -	- -	+	+-	- -	+	<u> </u>	7-		_	-		-		
	8 8	- 1				- 1	L						i			- 1							
l á í	1. č ~ l					1	[
. Š	26. 0 R																						
Sheet	8 ⁷			_			-						+-	-	-	-							
. \$ \$	8 ⁷			+	+-		-	+		-		-	+-	1				-					
Sp.	Mileag 2 2 2 2 2 2 2 2 3 3 3 3 3 3 3 3 3 3 3				+		-	- +-					-										
	Mileag 25. 2 Intervening Distance																						
She.	Willing And State Of																						
23. [24.	Kiding Surface Type Right-of-Way Right-of-Way Distance																						
23. [24.	Operation Office In Right-of-Way 1799																						
tion 22. 23. 24.	One-Way Operation K ding Surface Type Utilities in Kight-of-Way																						
tion 22. 23. 24.	One-Way Operation K ding Surface Type Utilities in Kight-of-Way																						
tion 22. 23. 24.	One-Way Operation K ding Surface Type Utilities in Kight-of-Way																						
tion 22. 23. 24.	One-Way Operation K ding Surface Type Utilities in Kight-of-Way																						
tion 22. 23. 24.	Permitted 21. 22. 23. 24. 27. 26. 27. 27. 28. 28. 28. 29. 29. 29. 29. 29																						
Maint. Section 22. [23. [24.	One-Way Operation K ding Surface Type Utilities in Kight-of-Way																						
Maint. Section 22. [23. [24.	Permitted 21. 22. 23. 24. 27. 26. 27. 27. 28. 28. 28. 29. 29. 29. 29. 29																					-	
Maint. Section 22. [23. [24.	Pocking 20. 21. 22. 21. 22. 23. 24. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 26. 26. 26. 26. 26. 26. 26. 26. 26																						
3. Maint. Section 22. [23. [24.	20. Side walks 21. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2.																						
3. Maint. Section [19. 12. 12. 12.	Pocking 20. 21. 22. 21. 22. 23. 24. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 27. 26. 26. 26. 26. 26. 26. 26. 26. 26. 26																						
1. Maint. Section 19. 19. 121.	Curbs o Curbs Sidewolks Sidewolks Type																						
Maint. Section 2. [23. [24.]	Curb to Curb a C																						
US SR Maint. Section 118. 119. Adint. Section	Curb to Curbs Side wolks Side wolks Type Type Type Type Type Riding Surface Type Type Type Type Riding Surface Type Typ																						
US SR Maint. Section 118. 119. Adint. Section	Rights 6. With the control of the co																						
Route SR 19 Maint. Section 21 (23 (24)	Highways Highways Right: 0. 104 Surface (17) Curb to Curb Sidewalks Dorwalks Type One-Way Operation Right-of-Way Right-of-Way One-Way One-Way Right-of-Way Right-of-Way																						
US SR Maint: Section 118. 119. Adint: Section	Entrences Highways Right: 0. Web Sidewalks Curb to Curb Type One-Way One-Way Curbs Type Right-of-Way Right-of-Way Type One-Way Right-of-Way Type Right-of-Way																						
Route SR 19 Maint. Section 21 (23 (24)	Curbs Cu																						
Route SR 19 Maint. Section 21 (23 (24)	Entrences Highways Right: 0. Web Sidewalks Curb to Curb Type One-Way One-Way Curbs Type Right-of-Way Right-of-Way Type One-Way Right-of-Way Type Right-of-Way																						
Route SR 19. Maint. Section 15. 12. 12. 124.	Appendents 3. Appendents 4. Appendents 4. Appendents 5. Appendents 6. Appendents 6. Appendents 6. Appendents 7. Appendents 6. Appendents 7. Append																						
Route SR 19. Maint. Section 15. 12. 12. 124.	Apartements 13 Apartements 13 Apartements 13 Apartements 14 Apartements 14 Apartements 15																						
Route SR 3. Maint. Section 115. 118. 19. 121.	industrial 1. 1998 A pertreents 2. 1998 A pertreents 3. 1998 A prosess 4. 1998 Company Company 5. 1998 Company Company 6. 1998 Company Company 6. 1998 Company Company 6. 1998 Company 6.																						
2. Route SR 3. Maint. Section 115. 118. 19. 22. 23. 24.	industrial 1. 1998 A pertreents 2. 1998 A pertreents 3. 1998 A prosess 4. 1998 Company Company 5. 1998 Company Company 6. 1998 Company Company 6. 1998 Company Company 6. 1998 Company 6.																						
2. Route SR 3. Maint. Section 15. 18. 19. 121	industrial 1. 1998 A pertreents 2. 1998 A pertreents 3. 1998 A prosess 4. 1998 Company Company 5. 1998 Company Company 6. 1998 Company Company 6. 1998 Company Company 6. 1998 Company 6.																						
2. Route SR 3. Maint. Section 15. 18. 19. 121	School 1. Curbs School 2. Curbs School 3. Curbs School 3. Curbs School 3. Curbs School 4. Curbs School 5. Curbs School 6. Curb																						
2. Route SR 3. Maint. Section 15. 18. 19. 121	School																						
2. Route SR 3. Maint. Section 115. 118. 19. 22. 23. 24.	School 1. Curbs School 2. Curbs School 3. Curbs School 3. Curbs School 3. Curbs School 4. Curbs School 5. Curbs School 6. Curb																						

URBAN STATE NIGHWAY INVENTORY DATA SHEET

٠				
				. =
				1
		•		
				•

STATE HIGHWAY BRIDGE INVENTORY DATA SHEET


			 			 	_	
		Condition 2						
	Floar							
der	ļ	a allowabi 2				 		Notes s
s. Recorder_		Railing Type						
5	-56	© noitibno D	+	-	+-		\dashv	
		Vertical 7						38.
	4007	% lpinetoM						Trucks
	Superstructure							w inested
	ľ	ed/ ₁						[∞] T0A
	_	15.			+			Sarvice
Date		7. dign•J						. Buingis
	Spans	S. YedmuM						Safe Lood (1moT)
	_	Ta Rail						e6∀
9	₩idth	oT dnu D			-			e avodA serow AgiH
		Length		+	+-		\dashv	De yourself
Sheet	<u>.</u>	llo1evO					\Box	F. evodA
3		Number						A Approach 25. 26. 26. 26. 26. 26. 26. 26. 26. 26. 26
	oʻ.	taertrea				_	_	
		Number						42 • noitibno
†ion	œ,	Structure						Substitution 23.
÷ Sec		e e	 -			 .	_	<u> </u>
2. - Maint. Section	7.	Odometer						Odometer Reading
		Location						Location
Route SR								

	-		
•			

STATE HIGHWAY RAILROAD PROTECTION DATA SHEET


Motes Notes Total To	Route SR	2. Maint. Section			3. Sheet_)et	of	. .)ate			y der		
7. 23. ADV Notes		7. Odometer Reading	salenT Per Dey	2 - ujəm	Approx. S. rains		Protectio	Po elgnA gntason	16. Sight Distance 300 Feet from Track	17. Obstructio To Vistbilit		Candition Of Approaches		of Greeks
Odemeter Reading ADV				-	T	13 T		,	├ - ├-	 		├ <i>-</i> -	o	
Odometer Reading ADV														
7. Oddmeter Reading ADV														
Odometer Reading ADV										- -		_		
Odemator Reading ADV										-		_		
Odometer Reading ADV											_	_ -		
Reading ADV		7.	21.	22.										
	Location	Odometer Reading	ADV						Notes					

				0.5
		-		




	· .		


PRIMARY STATE HIGHWAYS



SECONDARY STATE HIGHWAYS



COUNTY PRIMARY ROADS




BITUMINOUS SURFACE TREATMENT

TOLERABLE STANDARDS FIGURE 8


	•		
			,
		•	

PRIMARY STATE HIGHWAYS




HIGH TYPE PAVEMENT

SECONDARY STATE HIGHWAYS



COUNTY PRIMARY ROADS



STANDARDS FOR NEW CONSTRUCTION

FIGURE 9




SAMPLE SUMMARY OF IBM. TABULATIONS

	rear TYPE OF COGNECTOR CONSTRUCTION FRESCO WECESSARY	GCONSTRUCTON LAME DYDGED HIGHWAY DIMETS	ACCESS RECONSTRUCTION A _ANE DVINCO LIGHTAN - LOWERS	ACCOUNTED TO THE PARTY OF THE P	PIDEN C EESLEPICE TO ZA	WIDEN 4
	rtat Cochucto rteco	556	556	55.61	3 35 7	956
	RIGHT TOPOGRAPHY YEAR OF WAY CONSTRUK (FEET) WEDG	FLAT	FLA	FLAT	ROLLING	ROLLING
	EIGHT OF WAY	5	5	5	3	9
	GEADE	# # n o	0 0 0	0.5%	3-62.	0-97.
	CURVE	NOME	SOME	NONE	SOME	SOME
	SHOULDER CLAVE WIDTH (FEET	ı	1	1	=	=
	SURFACE CONDITION	MEDIUM(9-152)	MEDIUM (2-62)	MEBUM(5-15)	CRITICAL (over soft)	CRITICAL (Over 30%)
	SUBFACE CONSTRUCTION	076	1940	7261	16.91	1831
	YEAR OF MAJOR	UNKNOWN	1924	1919	2161	1917
2	NGO DE SUBEACE TOTAL THICK- TEAP OF TERE OF SUBFACE SUBFACE TERRELE THICK-NESS HESS OF BASE MAJOR SUBFACE COMPITION PANYMERT (NOTHES) THICKNESS (NEXT CONSTRUCTION) CONSTRUCTION CONSTRUCTI	Ðι	σ,	UNENOWAL	UHKNOWN	NAKNOWN
INFORMATION	SUPFACE THICK NESS (*NCHES)	\$ 2	1 6 R	6-1 6	6-1-6	9-7-6
	RIGID OR FLEXIBLE PAVE MENT	FLEXIBLE	FLEXIBLE	RIGID	RIGID	PIGID
HIGHWAY	SURFACE	ASPHALT	12,400 SANG ASPHALT FLEXIBLE	SAND CONCRETE	2,400 AUUVIUM CONCRETE	2400 ALLIWIUM CONCRETE
	SOIL	SAND	SANG	SAND	AUUVIU	ALLUVIUM
	PSS TEAFFIC (VEHICLES PEP DAY)	15,200 SAND	12,400	2,500		2,400
	CAPACITY (VEMICLES PER DAV)	ξ,		100	, 500	4,000
	"MANTHANCE SUBSECTION HIGHTARY SUBSECTION PARENERS GROUD BATE CARATITY PSS TEASTS SOLUTIVE SUBSECTION HUMBER DISTRICT LENGTH ANDTH KNO ACCIDENTS FOR (KENCLES (VEHICLES TYPE LETT) WOOMSTE (MINES) (FEET) MOODOWEHICHE FEE DAY) FEE DAY)	89	œ	<u>8</u> 2	216	21b
	PAVEMENT WIDTH (FFET)	52	\$ 2	23	02	20
	SUBSECTION LENGTH (MRLES)	5 2	0 2	5.5	5	<u>.</u>
	HIGHVAY SUBSECTION DISTRICT LENGTH HOMBER (MEES)	CRAWFORDS-	CEAVFORDS	CRAWFORDS-	CFAUFORDS VIELE	CPAVEGEUS
	SUBSECTION HUMBER	-	-	2	-	2
	MUNTENANCE S *ECTION LETTER	<u>.</u>	K-2	ķ.	-	ı
1	ROUTE	U3 41	th cu	us 41	38 43	SR 43
		1				

	BRIDGE TYPE OF WANDER STRICTURE	UNENOVH COMCULTE ANCH CROSSING	CA76-11 CONCRETE ABEN FORMA	NI V SCRSA CONCRETE ACACEDSSING		109 5744
		PEINFORCED STYEAM COMCULTE ANCH CROSSING	PENHFORCED STREAM	416 0308 416 0308		STEEL TRUSS SHEAR P
ಪ	(313) (310) (310) (310)	SAM Sec	CAM 24	S 8 8		7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
PIDGE	TH (TT)	103		5		1
BRIDGE INFORMATION	TH HUMB			-		
DEMATIO	SE POSTCI LOAGHE S (TOWS)	07	02	3		5
Z.	STRVICE ON CLEAP LEWGTH HUMBER DOSTED GERM YNTERS WENDER CLEAP YNTHER CLEAP YNTHER CREAT STRUCK TARE STOVE AND THE CREAT STRUCK TARE STRUC	UMFNOWR	4	J		* (
	VERTICAL CITAL MANCE OF STREAM	<u> </u>	07	72		ng (
	STARES .	62	5	-		0
RAILROA	YEAR STRUCTURE HELDED	1755	544	, 24.		1454
D CRO	PAIL BOAD NAME	CHICAGO, MILVAUKEE SE BAUL 6 PACIFIC		-		
SSING	PPLS TRACING. NUMBER OF TRAINS	CHICAGO, MICHALS SIGNALS ST PAUL (15,200 SIGNALS PACIFIC				
RAILROAD CROSSING INFORMATION	TYPE OF PROTECTION	SIGNALS				
ATION	NAME INSTITUTED OF TEAS CARD HIGHWAY NAME IN SPERKING CONSTRUCTION SEPARATOR CONSTRUCTION TANKS OF TRAINS	1955				
	PPS TRAIN TIPE OF TEAK CHAIN HIGHWAY CHINCE CALLEGAD REGAT FALCIDAD TOTAL NUMBER PROTECTION SEPRENTIAL CONTRACTION COMMENTATION SEPRENTIAL CONTS CONTS CONTS CONTS	000'000	000, 211 000, 031	0.270,000	140,000	
	COMPARATION COSTS		176,000	# 1,000		
.00	CULROAD RIGHT RALEGAD TOTAL SEPARATION CONTRACCONTS. CONTRACCONTS. CONTRACTOR	000, 251 000, 362 000, 811				•
INI IS	RIGHT OF WAY COSTS	125 (000)	000, 21	000,543		
COST INFORMATION	PROTECTION COSTS					•
NO	TOTAL CONSTRUCTION COSTS	800° K 1'1	ar'ex		ow.01	
	MANTAMATI AP	ED PROBLEMS THE SECTION ON POR	PATRICIA CALLE TO CAL OR (CA.	MINISTER OF THE METAL STATE OF	TOO THE THE PROPERTY OF THE PR	PROTECTION CONTRACTOR
	4.4 57 24TD COS13	מיינים ישו	SESTERITOR SALE L. 20	CASTRACTO	MANUFACTOR	W. Tak Die

FIGURE 10


		that		



ANNUAL AVERAGE COST FOR 15 YEAR PROGRAM
FIGURE 11

^{*} CORRECTED TO COSTS OBTAINED FROM SECTION 108(d) STUDY

			-
	٠.		
	/		



ESTIMATED REVENUES & NEEDS FIGURE 12

	•	

